

Vintage Racer Group Tire Rules

Updated: 1/6/2020

- Sizing is based on existing rules and regulations for individual car classification.
- Tread must extend across the tire (no DOT slicks with only circumferential grooves).
- Minimum 2/32nds of measurable tread.
- Minimum UTQG of 100 AAA.
- Minimum speed rating of H.

Some examples of acceptable tires:

Avon ACB10, Goodyear Blue Streak, Hoosier Street TD & Speedster, Toyo RA1, R888- R888R, R1R

Some examples of non-acceptable tires:

Slicks or any of the following tires: Avon Tech RA, BFG G -Force R1, Goodyear GS/CS/RS, Hankook Z214, Hoosier DOT Radial, (A6 or R6), Kumho V710, Toyo RR, or any other “street slick” type DOT tire.

NON-DOT Racing Tires:

The non-DOT treaded racing tires listed below are approved for VRG competition:

- Avon: ACB9, CR6ZZ, A29, H-003 and H-009
- Goodyear: BlueStreaks, Vintage Sports Car Specials, G12 and G12A
- Hoosier: Vintage TD, Street TD, Speedster, TDR, TDS, R35B, and VFF
- Dunlop: L-series, M-series, CR65, and CR82

Any non-DOT racing tire that is not listed above, is not approved for VRG competition.

Contact:

Specific tire questions may be submitted to the chair of the VRG Eligibility Committee:

Jim Karamanis, jim@vrgonline.org